

SAFETY DATA SHEET

Issuing Date 15-May-2015	Revision Date 24-July-2015 Revision Number 1		
1. IDENTIFICATION	OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING		
GHS Product Identifier			
Product Name:	SealBest 1000 Advanced Thermoplastic Modified Driveway Sealer and Filler		
Other Means of Identification			
Product Code(s):	H5411		
Synonyms	None		
Recommended Use of the Chemical	and Restrictions on Use		
Recommended Use:	No Information Available		
Uses Advised Against:	No information Available		
Supplier's Details			
Manufacturer Address ThorWorks Industries, Inc. 2520 S. Campbell St. Sandusky, OH 44870 <u>www.sealbest.com</u> 1-800-326-1994			
Emergency Telephone Number			
Emergency Telephone Number	Chemtrec 1-800-424-9300		
2. HAZARDS IDENTIFICATION			
<u>Classification</u>			
This chemical is not considered ha	zardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).		
GHS Label Elements, Including Precautionary Statements			
Emergency Overview			

Signal Word	Warning	
•Harmful if •May caus	swallowed e skin irritation	
Appearance: Black	Physical State: Liquid	Odor: Asphaltic

Precautionary Statements

ionary Statements		
Prevention	Inhalation:	May cause irritation of respiratory tract.
	Eye Contact:	Contact with eyes may cause irritation.
	Skin Contact:	May cause irritation.
	Ingestion:	Ingestion may cause stomach discomfort.
General Advice	●None	
Storage	 Keep container tightly 	/ closed
Disposal	 Dispose of material/co 	ontainers in accordance with the appropriate state

•Dispose of material/containers in accordance with the appropriate state, regional, or local regulations.

Hazard Not Otherwise Classified (HNOC)

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %	Trade Secret
Limestone	1317-65-3	20-40	*
Asphalt	8052-42-4	20-40	*
Quartz	14808-60-4	<20	*
Kaolin	1332-58-7	<10	*
Bentonite	1302-78-9	<10	*

*The exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of Necessary First-Aid Measures

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions, see a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician if necessary.

Most Important Symptoms/Effects, Acute and Delayed

Most Important Symptoms/Effects No information available

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician

Treat Symptomatically. May cause sensitization by skin contact.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon Dioxide (CO₂). Dry Chemical. Foam. Water Fog.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

No information available

Explosion Data	
Sensitivity to Mechanical Impact	None
Sensitivity to Static Discharge	None

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure- demand MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Personal Precautions:	Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.
Environmental Precautions	
Environmental Precautions:	See Section 12 for additional Ecological Information
Methods and Materials for Containm	ent and Cleaning Up
Methods for Containment:	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up:	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for Safe Handling			
Handling:	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, and clothing. Wear personal protective equipment. Avoid breathing vapors or mists. Do not eat, drink, or smoke when using this product. Wash thoroughly after handling.		
Conditions for Safe Storage, Including Any Incompatibilities			
Storage:	Keep container tightly closed		
Incompatible Products:	Strong oxidizing agents. Acids.		
	8. EXPOSURE CONTROLS / PERSONAL PROTECTION		

Control Parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone 1317-65-3	-	TWA: 15 mg/m ³ TWA: 5 mg/m ³ (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³	TWA: 5 mg/m³ respirable dust TWA 10 mg/m³ total dust
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m³ fume 15 min.
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	30/(%SiO2+2) mg/m ³ TWA, Total Dust; 250/(%SiO2+5) mppcf TWA, respirable fraction; 10/(%SiO2+2) mg/m ³ TWA, respirable TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust
Kaolin 1332-58-7	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA 5 mg/m ³ respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Bentonite 1302-78-9	TWA 1 mg/m ³ respirable fraction	-	-

Appropriate Engineering Controls

Engineering Measures:

Showers Eyewash Stations Ventilation Systems

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Skin and Body Protection: Respiratory Protection:	If splashes are likely to occur, wear: Safety glasses with side shields. Impervious gloves. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State: Liquid Odor: Asphaltic		Appearance: Odor Threshold:	Black No Information Available
<u>Property</u> pH Melting Point/Range Boiling Point/Boiling Range Flash Point Evaporation Rate Flammability (solid, gas) Flammability Limits in Air	Values No data available No data available 100° C No data available No data available No data available	Remarks/Method None known None known None known None known None known None known	
Upper flammability limit Lower flammability limit Vapor Pressure Vapor Density Specific Density Water Solubility Solubility in other solvents Partition coefficient: n-octanol/water Autoignition Temperature Decomposition Temperature Viscosity	No data available No data available No data available No data available 1.29 @ 77 F Easily dispersible No data available No data available No data available No data available No data available No data available	None kno None kno None kno None kno None kno None kno None kno None kno	own own own own own own own
Flammable Properties	Not Flammable		
Explosive Properties Oxidizing Properties	No data available No data available		
Other Information			
VOC Content	Less than 15 g/l		
	10. STABILITY AND REACTIVITY		1
Reactivity:	No data available		
Chemical Stability:	Stable under recommended storage conditions.		
Possibility of Hazardous Reactions:	None under normal processing.		
Hazardous Polymerization:	Hazardous polymerization does not occur.		
Conditions to Avoid:	None known		

Hazardous Decomposition Products: Carbon Monoxide (CO), Carbon Dioxide (CO²), Hydrogen Sulfide, Nitrogen Dioxide

Strong oxidizing agents. Acids.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Incompatible Materials:

 Product Information
 May cause irritation

 Inhalation:
 May cause irritation

 Eye Contact:
 Contact with eyes

 Skin Contact:
 May cause irritation

 Ingestion:
 Ingestion may cause

May cause irritation of respiratory tract. Contact with eyes may cause irritation. May cause irritation. Ingestion may cause stomach discomfort.

Chemical Name	LD50 Oral	LD50 Dermal	LD50 Inhalation
Asphalt	5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-
Quartz	500 mg/kg (Rat)		
Bentonite	>5000 mg/kg (Rat)	-	-

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics

Symptoms:

No information available.

Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Sensitization:	
Mutagenic Effects:	
Carcinogenicity:	

No information available. No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen. The IARC, NTP, and OSHA do not list asphalt as a carcinogen. In general, the oxidation of polycyclic aromatic hydrocarbons destroys their carcinogenic potential. Petroleum asphalt, shale oil asphalts, and coal tars show distinct variation in their relative carcinogenicity for experimental animals. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt	A3	Group 2B	Reasonably Anticipated	Х
Quartz	A2	Group 1	Known	Х

ACGIH: (American Conference of Governmental Industrial Hygienists) A3 – Animal Carcinogen A2 – Suspected Human Carcinogen IRAC: (International Agency for Research on Cancer) Group 2B – Possibly Carcinogenic to Humans Group 1 – Carcinogenic to Humans NTP: (National Toxicity Program) Reasonably Anticipated – Reasonably Anticipated to be a Human Carcinogen Known – Known Human Carcinogen OSHA: (Occupational Safety & Health Administration) X – Present

Reproductive Toxicity:	No information available.
STOT - Single Exposure:	No information available.
STOT – Repeated Exposure:	No information available.
Aspiration Hazard:	No information available.

Numerical Measures of Toxicity – Product

The following values are calculated based on Chapter 3.1 of the GHS document

LD50 Oral: LD50 Dermal 12542 mg/kg; Acute toxicity estimate 6181 mg/kg, Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Bentonite 1302-78-9		LC50 96 h: 8.0-19.0 g/L (Salmo gairdneri) LC50 96 h: = 19000 mg/L static (Oncorhynchus mykiss)		

Persistence and Degradability: No

No information available.

Bioaccumulation

Chemical Name	Log Pow
Asphalt	6.006

Other Adverse Effects:

No information available.

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Methods:	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging:	Do not re-use empty containers.
	14. TRANSPORTATION INFORMATION
DOT:	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA - Complies DSL/NDSL - Complies

Legend TSCA – United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS Number	Weight %	SARA 313 – Threshold Values %
Asphalt	8052-42-4	20-40	0.1

<u>SARA</u>	311/31	2 Hazard	Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65:

Chemical Name	CAS Number	California Prop. 65
Quartz	14808-60-7	Carcinogen

U.S. State Right-To-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Limestone	Х	Х	Х		Х
Asphalt	Х	Х	Х		Х
Quartz	Х	Х	Х	-	Х
Kaolin	Х	Х	Х		Х

U.S. EPA Label Information

EPA Pesticide Registration Number:

Not applicable

	16. OTHER INFORMATION				
<u>NFPA</u>	Health Hazard: 1	Flammability: 0	Instability: 0	Physical and Chemical Hazards-	
<u>HMIS</u>	Health Hazard: 1	Flammability: 0	Physical Hazard: 0	Personal Protection: X	
Revision Date: Revision Note:	24-July-2015 Supersedes 1	5-May-2015.			

<u>General Disclaimer</u> The information provided on this SDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.