SAFETY DATA SHEET



Issuing Date 9-April-2015

Revision Date 31-Aug-2015

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

<u>GHS Product Identifier</u> Product Name:	SealBest Blacktop Crack Filler		
<u>Other Means of Identification</u> Product Code(s):	H5550		
Synonyms	None		
<u>Recommended Use of the Chemical</u> Recommended Use:	and Restrictions on Use No Information Available		
Uses Advised Against:	No Information Available		
Manufacturer's Details Manufacturer Address ThorWorks Industries, Inc. 2520 S. Campbell St. Sandusky, OH 44870 www.sealbest.com 1-800-326-1994			
Emergency Telephone Number Emergency Telephone Number	Chemtrec 1-800-424-9300		
	2. HAZARDS IDENTIFICATION		

Classification

This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

GHS Label Elements, Including Precautionary Statements

		Emergency Overview	
Signal Word	Warning		
\wedge			
	armful if swallowed ay cause skin irritation		
		Physical State: Liquid	Odor: Asphaltic
●M Appearance: Black Precautionary Statemer	ay cause skin irritation	Physical State: Liquid	Odor: Asphaltic
●M Appearance: Black Precautionary Statemer Prevention	ay cause skin irritation ts •None	Physical State: Liquid	Odor: Asphaltic
●M Appearance: Black Precautionary Statemer	ay cause skin irritation ts •None	Physical State: Liquid	Odor: Asphaltic

COMPOSITION/INFORMATION ON INGREDIENTS 3.

Chemical Name	CAS Number	Weight %	Trade Secret
Asphalt	8052-42-4	40-60	*
Kaolin	1332-58-7	10-20	*
Polymer Blend	Proprietary	0-15	*

*The exact percentage of composition has been withheld as a trade secret.

FIRST AID MEASURES 4.

Description of Necessary First-Aid Measures				
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.			
Skin Contact	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions, see a physician.			
Inhalation	Move to fresh air. If symptoms persist, call a physician.			
Ingestion	Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician if necessary.			

Most Important Symptoms/Effects, Acute and Delayed

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician

Treat Symptomatically. May cause sensitization by skin contact.

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u> Carbon Dioxide (CO₂). Dry Chemical. Foam. Water Fog.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

No information available

Explosion Data	
Sensitivity to Mechanical Impact	None
Sensitivity to Static Discharge	None

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure- demand MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures			
Personal Precautions:	Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.		
Environmental Precautions Environmental Precautions:	See Section 12 for additional Ecological Information		
Methods and Materials for Containment and Cleaning Up			
Methods for Containment:	Prevent further leakage or spillage if safe to do so.		
Methods for Cleaning Up:	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.		

7. HANDLING AND STORAGE

Precautions for Safe Handling Handling:

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, and clothing. Wear personal protective equipment. Avoid breathing vapors or mists. Do not eat, drink, or smoke when using this product. Wash thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities			
Storage: Keep container tightly closed			
Incompatible Products:	Strong oxidizing agents. Acids.		

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Control Parameters</u> Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m³ fume 15 min.
Kaolin 1332-58-7	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA 5 mg/m ³ respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable dust

Appropriate Engineering Controls Engineering Measures:

ing Measures:	Showers
	Evewash

Eyewash Stations Ventilation Systems

Individual Protection Measures, such as Personal Protective Equipment			
Eye/Face Protection: Skin and Body Protection:	If splashes are likely to occur, wear: Safety glasses with side shields. Impervious gloves.		
Respiratory Protection:	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.		
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State:LiquidOdor:Asphaltic		Appearance: Odor Threshold:	Black No Information Available
Property	Values	Remarks/Method	
рН	No data available	None kn	own
Melting Point/Range	No data available	None kn	own
Boiling Point/Boiling Range	100° C	None kn	own
Flash Point	No data available	None kn	own
Evaporation Rate	1.8	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor Pressure	No data available	None kn	own
Vapor Density	<1	None known	
Specific Density	1.15 @ 77 F	None kn	own

Property Water Solubility Solubility in other solvents Partition coefficient: n-octano Autoignition Temperature Decomposition Temperature Viscosity Flammable Properties Explosive Properties Oxidizing Properties	Values Easily disper No data ava No data ava No data ava No data ava No data ava No data ava No tata ava No data ava No data ava No data ava	ilable ilable ilable ilable ilable ble ilable	Remarks/Methoc None known None known None known None known None known None known	1	
Other Information VOC Content	Less than 15	5 g/L			
	10	D. STABILITY AND RE	EACTIVITY		
Reactivity: No data available Chemical Stability: Stable under recommended storage conditions. Possibility of Hazardous Reactions: None under normal processing. Hazardous Polymerization: Hazardous polymerization does not occur. Conditions to Avoid: None known Incompatible Materials: Strong oxidizing agents. Acids. Hazardous Decomposition Products: Carbon Monoxide (CO), Carbon Dioxide (CO ²), Hydrogen Sulfide, Nitrogen Dioxide					
	11.	TOXICOLOGICAL INF	FORMATION		
Information on Likely Routes of Exposure Product Information Inhalation: May cause irritation of respiratory tract. Eye Contact: Contact with eyes may cause irritation. Skin Contact: May cause irritation. Ingestion: Ingestion may cause stomach discomfort.					
Chemical Name	LD50 Or	al LD	50 Dermal	LD50 Inhalation	
Asphalt	5000 mg/kg		mg/kg (Rabbit)	-	
Symptoms Related to the Physical, Chemical, and Toxicological Characteristics Symptoms: No information available. Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure Sensitization: No information available. Mutagenic Effects: No information available. Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen. The IARC, NTP, and OSHA do not list asphalt as a carcinogen. In general, the oxidation of polycyclic aromatic hydrocarbons destroys their carcinogenic potential. Petroleum asphalt, shale oil asphalts, and coal tars show distinct variation in their relative carcinogenicity for experimental animals.					
	shale oil asp	halts, and coal tars show	distinct variation in th	neir relative carcinogenicity for	
Chemical Name	shale oil asp	halts, and coal tars show	distinct variation in th	neir relative carcinogenicity for OSHA	

ACGIH: (American Conference of Governmental Industrial Hygienists) A3 – Animal Carcinogen IRAC: (International Agency for Research on Cancer) Group 2B – Possibly Carcinogenic to Humans NTP: (National Toxicity Program) Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity:	No information available.
STOT - Single Exposure:	No information available.
STOT – Repeated Exposure:	No information available.
Aspiration Hazard:	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Persistence and Degradability: No information available. Bioaccumulation

Chemical Name		Log Pow	
Asphalt		6006	
Other Adverse Effects:	No information available.		
	13. DISPOS	AL CONSIDERATIONS	
Waste Disposal Methods:	Methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.		
Contaminated Packaging:	Do not re-use empty containers.		
	14. TRANSPO	RTATION INFORMATION	
DOT:	Not regulated		
	15. REGULA	ATORY INFORMATION	

International Inventories TSCA – Complies DSL/NDSL – Complies

Legend

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL – Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS Number	Weight %	SARA 313 – Threshold Values %
Asphalt	8052-42-4	20-40	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65:

This product does not contain any Proposition 65 chemicals.

U.S. State Right-To-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Asphalt	Х	Х	Х		Х
Kaolin	Х	Х	Х		Х
Carbon Black	Х	Х	Х	Х	Х

U.S. EPA Label Information EPA Pesticide Registration Number:

Not applicable

	16. OTHER INFORMATION					
<u>NFPA</u>	Health Hazard: 1	Flammability: 0	Instability: 0	Physical and Chemical Hazards-		
<u>HMIS</u>	Health Hazard: 1	Flammability: 0	Physical Hazard: 0	Personal Protection: X		

31-Aug-2015 **Revision Date: Revision Note:** Supersedes 9-April-2015

<u>General Disclaimer</u> The information provided on this SDS is correct to the best of our knowledge, information, and belief at the date of its processing, storage, transportation publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.