## SAFETY DATA SHEET



**Issuing Date** 15-May-2015

Revision Date 24-July-2015

**Revision Number** 1

#### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS Product Identifier Product Name:

SealBest Acrylic-Modified Trowel Grade Crack Filler

Other Means of Identification Product Code(s): SKU #: Synonyms

H5700 558-1714 None

Recommended Use of the Chemical and Restrictions on UseRecommended Use:No Information AvailableUses Advised Against:No information Available

Supplier's Details Manufacturer Address ThorWorks Industries, Inc. 2520 S. Campbell St. Sandusky, OH 44870 www.sealbest.com 1-800-326-1994

Emergency Telephone Number

Chemtrec 1-800-424-9300

#### 2. HAZARDS IDENTIFICATION

#### **Classification**

This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

#### GHS Label Elements, Including Precautionary Statements

		Emergency Overview		
Signal Word	Warning			
	nful if swallowed v cause skin irritation			
eway	cause skin initiation			
Appearance: Black		Physical State: Mastic	Odor:	Asphaltic
recautionary Statements Prevention	Inhalation:	May cause irritation of respiratory tract.		
	Eye Contact: Skin Contact:	Contact with eyes may cause irritation.		
	Skill Contact.	May cause irritation.		
General Advice	Ingestion: •None	Ingestion may cause stomach discomfort.		
General Advice Storage	Ingestion:	Ingestion may cause stomach discomfort.		

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %	Trade Secret
Attapulgite	12174-11-7	0-10	*
Asphalt	8052-42-4	10-30	*
Quartz	14808-60-4	40-70	*
Polymer	Proprietary	<5	*

\*The exact percentage of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

Description of Necessary First Aid N	
Description of Necessary First-Aid N Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a
Lye contact	physician.
Skin Contact	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic
	reactions, see a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an
-	unconscious person. Consult a physician if necessary.
Most Important Symptoms/Effects, /	
Most Important Symptoms/Effects	No information available
Indication of Immediate Medical Atte	ention and Special Treatment Needed. If Necessary
Notes to Physician	Treat Symptomatically. May cause sensitization by skin contact.
Noted to Physician	
	5. FIRE-FIGHTING MEASURES
	5. FIRE-FIGHTING MEASURES
Suitable Extinguishing Media	
Suitable Extinguishing Media Carbon Dioxide (CO <sub>2</sub> ). Dry Chemical. I	
Carbon Dioxide (CO <sub>2</sub> ). Dry Chemical. I	Foam. Water Fog.
Carbon Dioxide (CO <sub>2</sub> ). Dry Chemical. I	
Carbon Dioxide (CO <sub>2</sub> ). Dry Chemical. I Unsuitable Extinguishing Media	Foam. Water Fog. CAUTION: Use of water spray when fighting fire may be inefficient.
Carbon Dioxide (CO <sub>2</sub> ). Dry Chemical. I	Foam. Water Fog. CAUTION: Use of water spray when fighting fire may be inefficient.
Carbon Dioxide (CO <sub>2</sub> ). Dry Chemical. I Unsuitable Extinguishing Media Specific Hazards Arising from the C	Foam. Water Fog. CAUTION: Use of water spray when fighting fire may be inefficient.
Carbon Dioxide (CO <sub>2</sub> ). Dry Chemical. I Unsuitable Extinguishing Media Specific Hazards Arising from the C No information available Explosion Data	Foam. Water Fog. CAUTION: Use of water spray when fighting fire may be inefficient. hemical
Carbon Dioxide (CO <sub>2</sub> ). Dry Chemical. I Unsuitable Extinguishing Media Specific Hazards Arising from the C No information available	Foam. Water Fog. CAUTION: Use of water spray when fighting fire may be inefficient.

<u>Protective Equipment and Precautions for Firefighters</u> As in any fire, wear self-contained breathing apparatus pressure- demand MSHA/NIOSH (approved or equivalent) and full protective gear.

	6. ACCIDENTAL RELEASE MEASURES
Barra and Barra attinue Barta attinue E	
	guipment, and Emergency Procedures
Personal Precautions:	Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.
Environmental Precautions	
Environmental Precautions:	See Section 12 for additional Ecological Information
Methods and Materials for Contain	nent and Cleaning Up
Methods for Containment:	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up:	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.
	7. HANDLING AND STORAGE
<u>Precautions for Safe Handling</u> Handling:	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, and clothing. Wear personal protective equipment. Avoid breathing vapors or mists. Do not eat, drink, or smoke when using this product. Wash thoroughly after handling.

# Conditions for Safe Storage, Including Any Incompatibilities Storage: Keep container tightly closed

Incompatible Products:

Strong oxidizing agents. Acids.

#### **EXPOSURE CONTROLS / PERSONAL PROTECTION** 8.

# Control Parameters Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m <sup>3</sup> benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m³ fume 15 min.
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	30/(%SiO2+2) mg/m <sup>3</sup> TWA, Total Dust; 250/(%SiO2+5) mppcf TWA, respirable fraction; 10/(%SiO2+2) mg/m <sup>3</sup> TWA, respirable TWA: 0.1 mg/m <sup>3</sup> (vacated)	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust
Attapulgite 12174-11-7	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA 5 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable dust

# Appropriate Engineering Controls Engineering Measures:

Showers Eyewash Stations Ventilation Systems

Individual Protection Measures, s	uch as Personal Protective Equipment
Eye/Face Protection:	If splashes are likely to occur, wear: Safety glasses with side shields.
Skin and Body Protection:	Impervious gloves.
Respiratory Protection:	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on Basic Physical and Chemical Properties

Physical State:	Mastic	lenncal Properties	Appearance:	Black
•			Odor Threshold:	No Information Available
Odor:	Asphaltic		Odor Threshold:	No mormation Available
Property		Values	Remark	s/Method
pH		No data available	None kn	
Melting Point/Ran	00	No data available	None kn	
Boiling Point/Boil	•	100° C	None kn	
Flash Point	ing Range	No data available	None kn	
Evaporation Rate		No data available	None kn	
Flammability (soli		No data available	None kn	own
Flammability Limi				
Upper flammab	•	No data available		
Lower flammat	pility limit	No data available		
Vapor Pressure		No data available	None kn	own
Vapor Density		No data available	None kn	own
Specific Density		1.75 @ 77 F	None kn	own
Water Solubility		Easily dispersible	None kn	own
Solubility in other	solvents	No data available	None kn	own
Partition coefficie	nt: n-octanol/water	No data available	None kn	own
Autoignition Tem	perature	No data available	None kn	own
Decomposition Te		No data available	None kn	own
Viscosity	•	No data available	None kn	own
Flammable Prope	rties	Not Flammable		
Explosive Propert		No data available		
Oxidizing Propert		No data available		
Oxidizing Propert				
Other Information				
VOC Content		Less than 15 g/l		
+ CO Content				

Page 3 -

### **10. STABILITY AND REACTIVITY**

Reactivity: Chemical Stability:	No data available Stable under recommended storage conditions.
Possibility of Hazardous Reactions:	None under normal processing.
Hazardous Polymerization:	Hazardous polymerization does not occur.
Conditions to Avoid:	None known
Incompatible Materials:	Strong oxidizing agents. Acids.
Hazardous Decomposition Products:	Carbon Monoxide (CO), Carbon Dioxide (CO <sup>2</sup> ), Hydrogen Sulfide, Nitrogen Dioxide

#### **11. TOXICOLOGICAL INFORMATION**

#### Information on Likely Routes of Exposure

**Product Information** 

Inhalation: May cause irritation of respiratory tract. Eye Contact: Contact with eyes may cause irritation. Skin Contact: May cause irritation. Ingestion: Ingestion may cause stomach discomfort.

Chemical Name	LD50 Oral	LD50 Dermal	LD50 Inhalation
Asphalt	5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-
Quartz	500 mg/kg (Rat)		

### Symptoms Related to the Physical, Chemical, and Toxicological Characteristics

Symptoms:

No information available.

#### Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Sensitization: Mutagenic Effects: Carcinogenicity:

No information available. No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen. The IARC, NTP, and OSHA do not list asphalt as a carcinogen. In general, the oxidation of polycyclic aromatic hydrocarbons destroys their carcinogenic potential. Petroleum asphalt, shale oil asphalts, and coal tars show distinct variation in their relative carcinogenicity for experimental animals. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt	A3	Group 2B	Reasonably Anticipated	х
Quartz	A2	Group 1	Known	Х

ACGIH: (American Conference of Governmental Industrial Hygienists) A3 – Animal Carcinogen A2 - Suspected Human Carcinogen IRAC: (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans Group 1 - Carcinogenic to Humans NTP: (National Toxicity Program) Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen Known - Known Human Carcinogen **OSHA: (Occupational Safety & Health Administration)** X - Present **Reproductive Toxicity:** No information available. STOT - Single Exposure: No information available. STOT – Repeated Exposure: No information available. **Aspiration Hazard:** No information available.

#### **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

The environmental impact of this product has not been fully investigated.

#### Persistence and Degradability: No information available.

#### Bioaccumulation

Chemical Name	Log Pow
Asphalt	6.006

Other Adverse Effects:

No information available.

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Methods:	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging:	Do not re-use empty containers.
	14. TRANSPORTATION INFORMATION
DOT:	Not regulated

### **15. REGULATORY INFORMATION**

#### International Inventories

**TSCA –** Complies DSL/NDSL - Complies

Legend TSCA – United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

#### U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS Number	Weight %	SARA 313 – Threshold Values %
Asphalt	8052-42-4	20-40	0.1

#### SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

### Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific requirements at the local, regional, or state level pertaining to releases of this material.

### U.S. State Regulations

**California Proposition 65:** 

Chemical Name	CAS Number	California Prop. 65
Quartz	14808-60-7	Carcinogen

#### U.S. State Right-To-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Limestone	Х	Х	Х		Х
Asphalt	Х	Х	Х		Х
Quartz	Х	Х	Х	-	Х
Kaolin	Х	Х	Х		Х

#### U.S. EPA Label Information

**EPA Pesticide Registration Number:** 

Not applicable

16. OTHER INFORMATION				
<u>NFPA</u>	Health Hazard: 1	Flammability: 0	Instability: 0	Physical and Chemical Hazards-
<u>HMIS</u>	Health Hazard: 1	Flammability: 0	Physical Hazard: 0	Personal Protection: X
Revision Date: Revision Note:	24-July-2015 Supersedes 15-May-2015.			

<u>General Disclaimer</u> The information provided on this SDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.