

# Premium Fibered Aluminum Roof Coating



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

SealBest® Fibered Aluminum Roof Coating is a premium professional grade contractor proven blend of select waterproofing asphalts and high quality leafing aluminum pigments. When applied as directed, it cures to a brilliant decorative coating, providing maximum protection and durability against the elements. It reflects up to 90% of the sun's rays and reduces roof temperature by 15-20°F, increasing roof life and lowering energy costs.

## Uses

- Metal Roofs
- Concrete Roofs
- Built-Up Roofs
- MOD. Bitumen SBS/APP
- Weathered Asphalt Coatings
- Metal Buildings/Grain Bins
- Mobile Homes
- And More

## Surface Preparation

Repair all cracks, splits, and holes using SealBest Plastic Roof Cement and Asphalt Coated Glass Fabric, adhering to the directions on their label. Allow repairs to weather at least 30 days before coating. Clean surfaces thoroughly by brooming away dirt, dust and loose particulate. Remove all grease and oil using detergent and water, rinsing thoroughly. Broom away excess water and allow to dry completely.

## Application

Mix coating thoroughly before and during application. Uniformly coat the entire surface with the coating using a roofing brush or roller. Do not apply if rain or heavy dew is expected within 24 hours of application. Do not apply to wet or damp surfaces. Do not apply if temperature is expected to fall below 50°F within 12 hours of application. Clean up with waterless hand cleaner immediately after use. Do not apply to roofs which hold water. Standing water will result in premature failure.

## Drying Time

Allow 24 hours depending on weather conditions.

## Clean Up

While wet, use soap and water.

## Weather Conditions

- Do not apply if rain is imminent or forecast within 24 hours of application.

## Coverage (Approximate)

Metal Roofs: 75-100 sq. ft. per gallon  
Composition Roofs: 50-75 sq. ft. per gallon

## Precautions

- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F
- CAUTION! COMBUSTIBLE

## Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- CONTAINER MAY BE HAZARDOUS WHEN EMPTY as container may contain product residues and/or combustible vapors. All labeled hazardous precautions must be observed. Dispose of empty container in accordance with local, state or federal regulations
- Volatile Organic Content (VOC) is 500 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Ingredients:	Cas No.
Asphalt	8052-42-4
Stoddard Solvent	64742-88-7
Aluminum Flake	7429-90-5
Cellulose	9004-34-6
Calcium Carbonate	1317-65-3