

Non-Fibered Foundation Coating

Asphalt Based Coating



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

A cold-applied, liquid asphalt in a solvent system ideal for waterproofing above and below grade exterior concrete, masonry walls, and foundations that are completely dry. Dries black. Meets ASTM D 41.

Uses

Concrete Foundations

Surface Preparation

Surface must be clean, dry, and free of moisture both on and beneath the surface.

Application

Stir SealBest Non-Fibered Foundation Coating thoroughly. Apply a single coat over the entire surface with a brush, roller, or airless spray unit.

Drying Time

Allow material to dry and cure for 24 hours.

Clean Up

Clean tools with mineral spirits or waterless hand cleaner before material has dried.

Coverage (Approximate)

- Concrete and Masonry Surfaces: 50-65 sq. ft. per gallon

Precautions

- Do Not Heat or Thin
- Do Not Store at Temperatures Above 100 °F
- Do Not Apply Over Coal Tar Surfaces
- Do Not Apply Where Hydrostatic Pressures Could be Encountered
- Combustible. Contains Petroleum Distillate

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 250 gm/liter max
- Use with Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN

| Ingredients: | Cas No. |
|-------------------|------------|
| Petroleum Asphalt | 8052-42-4 |
| Mineral Spirits | 64742-88-7 |

Non-Fibered Foundation Coating - Asphalt Based Coating

Revised: 07/23